

LBB 3544/00

Standard Delegate Unit

- Compact, attractive delegate unit
- Built-in fold-away flat-panel loudspeaker
- Five voting buttons
- Cable connections located underneath the unit

The LBB 3544/00 is the standard delegate conference unit, enabling delegates to speak, register a request-to-speak, register a response request, listen to the speaker and vote. The flat-panel loudspeaker offers superior acoustics with minimal feedback, so increasing intelligibility. It is automatically muted when the microphone is activated. When the unit is not being used, the loudspeaker panel conveniently folds down. There are five voting buttons for parliamentary-, multiple choice- or audience response voting.



Microphones LBB 3549/00 and LBB 3549/50

This innovative, stylish and ergonomically-designed unit is equipped with a socket for a microphone (ordered separately) with an adjustable stem which simply plugs directly into the delegate unit for added convenience. The microphone has a unidirectional response for optimum performance even in noisy conditions, and includes a red indicator ring which illuminates when the microphone is on. Two microphones are available, with standard and extended stem lengths respectively.



Note: The microphones are separate type numbers, and must be ordered separately.

Controls and indicators

- Socket for pluggable condenser microphone (ordered separately) with built-in pop-and windshield, complete with light ring which illuminates when the microphone is on
- Built-in fold-away flat-panel loudspeaker, automatically muted if a microphone is on
- Microphone 'on/off' or 'request-to-speak' button
- Two 'Microphone on' indicators. One is located above the microphone on/off button (dual colour LED for 'request-to-speak' and 'microphone on' indication). The other is located on top of the loudspeaker.
- 'Request-to-speak' confirmation indicator (green LED)
- Five voting buttons with yellow LED confirmation indicators
These can be used to register:
 - PRESENT, NO (-), ABSTAIN (0), YES (+) (parliamentary voting)
 - Numerals: 1 to 5 (multiple choice or opinion polls)
 - Rating scale: - -, -, 0, +, ++ (audience response)
- 'De-init' switch on the underside of the unit



Connections

- 2 m (78.74 in) cable terminated in a moulded 6-pole circular connector
- 6-pole circular connector for loop-through connections
- 6-pole modular jack connector for Intercom Handset LBB 3555/00

Technical data for LBB 3544/00

Mounting	table-top (portable or fixed mounting) and flush-mounting	
Dimensions (H x W x D)	Table-top	50 x 275 x 155 mm (2.0 x 10.8 x 6.1 in)
	Flush-mounted	30 x 275 x 155 mm (1.2 x 10.8 x 6.1 in)
Weight	approx. 1.4 kg (3.1 lb)	
Colour	charcoal base (PH 10736) with silver panel	

Technical data for microphones (LBB 3549/00 and LBB 3549/50)

Mounting	5-pole XLR connector	
Stem length	LBB 3549/00	310 mm (12.2 in)
	LBB 3549/50	480 mm (18.9 in)
Weight	LBB 3549/00	approx. 110 g (0.2 lb)
	LBB 3549/50	approx. 125 g (0.3 lb)
Colour	charcoal (PH 10736)	