

LBB 3545/00

Delegate Unit with Channel Selector

- Channel selector for accessing interpretations
- 2-digit channel indicator display with backlighting
- Two headphone sockets, and one external microphone/headset microphone socket
- Two volume controls (left and right)
- Incorporates all functions of LBB 3544/00 Standard Delegate Unit

The LBB 3545/00 is stylistically and functionally similar to the LBB 3544/00 Standard Delegate Unit, but includes a built-in language channel selector. This makes it suitable for conferences where more than one language is used and simultaneous interpretations are available. The channel selector includes up and down select keys and a 2-digit display with backlighting, enabling rapid selection of the required language channel. Channel selection is automatically limited to the number of language channels available. The flat-panel loudspeaker offers superior acoustics with minimal feedback, so increasing intelligibility. When the unit is not being used, the loudspeaker panel conveniently folds down.

Note: The loudspeaker is not muted when the headphones/headset are connected.

Note: The pluggable microphone is automatically switched off when an external microphone is connected.

Note: For information about the pluggable microphones available for use with this unit, please refer to page 2.3.

Controls and indicators

- Channel selector with channel number display with backlighting and channel select keys (up/down)
- Headphone socket and volume control on each side of the unit
- Socket for external microphone or headset microphone
- Socket for pluggable condenser microphone (ordered separately) with built-in pop- and windshield, complete with a light ring which illuminates when the microphone is on.
- Built-in fold-away flat-panel loudspeaker
- Microphone on/off or request-to-speak button
- Two 'Microphone on' indicators. One is located above the microphone on/off button (dual colour LED for 'request-to-speak' and 'microphone on' indication). The other is located on top of the loudspeaker.
- 'Request-to-speak' confirmation indicator (green LED)
- Five voting buttons with confirmation indicators (yellow LEDs)
These can be used to register:
 - PRESENT, NO (-), ABSTAIN (0), YES (+) (parliamentary voting)
 - Numerals: 1 to 5 (multiple choice or opinion polls)
 - Rating scale: - -, - 0, +, ++ (audience response)
- 'De-init' switch on the underside of the unit

Connections

- 2 m (78.74 m) cable terminated in a moulded 6-pole circular connector
- 6-pole circular connector for loop-through connections
- 6-pole modular jack connector for Intercom Handset LBB 3555/00
- Left and right headphones sockets (3.5 mm (0.14 in) stereo jack type)
- Connection for external microphone or headset microphone (3.5 mm (0.14 in) stereo jack type).



Technical data

Mounting	table-top (portable or fixed mounting) and flush-mounting	
Dimensions (H x W x D)	Table-top	50 x 275 x 155 mm (2.0 x 10.8 x 6.1 in)
	Flush-mounted	30 x 275 x 155 mm (1.2 x 10.8 x 6.1 in)
Weight	approx. 1.4 kg (3.1 lb)	
Colour	charcoal base (PH 10736) with silver panel	